

Suggested Stack Up

1.4mil	5mil	L1 TOP LAYER	0.5oz Cu + 0.5oz Plate
0.7mil	4.7mil	L2 GND	0.5oz Cu
0.7mil	5mil	L3 PWR	0.5oz Cu
1.4mil	5mil	L4 BOTTOM LAYER	0.5oz Cu + 0.5oz Plate

Impedance Control	TraceWidth/Space	Impedance
Differential	4.5 / 7 / 4.5 (mil)	100 ohm 5%
Single Ended	5 (mil)	50 ohm 10%
Signal traces on L1 reference L2 plane & Signal traces on L4 reference L3 Plane		

* Manufacturer should change the stack up to match the impedance control base on the PCB material used.

MBCC-IO-PCB-D	AES-MBCC-IO-Rev.D
Ref Sch: U D	10/23/2013 1:35:38 PM
Board Thickness: 1.6mm 4 Layers FR4	
Top Solder	
Top Overlay	
Mechanical 1	
Mechanical 2	

Board shall be fabricate - Performance Class II as per IPC-6011 & IPC-6012
Material: Per IPC-4101A/24/26/29/99, Copper Clad,
High Temperature FR4 Class Epoxy Glass Rated UL940V-0,
0.5 OZ Copper for External Layers & 0.5 OZ Copper for Internal Layers.
Must be RoHS compliant & survive a Lead-Free Assembly Max reflow of 260 DEG C (6 Passes)
Td Rating: >340 DEG C
Z Axis CTE < 3.5%
Tg > 170 DEG C (Min)

Solder Mask: SMOBC Per IPC-SM-840C, Class T, Must be RoHS Compliant
TYP LPI, 0.0002 Min to 0.0008 Max measured over copper plating,
must clear all lands as indicated on gerber solder mask layers, (Color = Red)
Finish: Electro-less Nickel Immersion Gold (ENIG), 2~8 Micro Inches Gold Over 150~250 Mirco Inches Nickel
This Assembly shall be RoHS Compliant. Vendor shall deliver assembly with accompanying certificate of compliance.

