/SMARTEDGE AGILE Product Brief

Avnet part number: AVTSEA01a-M01a-S01a-C00

End to end solution to deliver Al and Security at the edge

The /SMARTEDGE AGILE meta-sensor, together with the Octonion IoT platform, form part of an end to end IoT solution that delivers AI and Security at the Edge. This hardware and software combination introduces a new Meta sensing category in the IoT market. The key advantage of this eco-system is to use the same solution for all stages of the IoT project – from proof of concept up to Industrialization.

Octonion **accelerates delivery of industrialized IoT solutions**, with higher performance, security and scalability, while significantly reducing costs.

The /SMARTEDGE AGILE meta-sensor is **CE/FCC certified**, and both hardware and software can be used directly for industrialized loT projects. The hardware is designed to allow a wide range of **sensor and connectivity boards**.

The platform is **optimized for Microsoft Azure Cloud** but can run on any public or private Cloud services. Best in class network security has been built in, based on **TLS security with ECC certificate** protecting you, your network, and your reputation from attack. Octonion is proven, robust and modular for faster and easier development and deployment.

With this hardware and software combo, you can **launch IoT projects three times faster** than with other platforms.



Use the same solution for all stages of your IoT project Build your own device based on the Brain



Octonion

ECOSYSTEM AND ENABLEMENT

- Octonion is your web-based development and visualization environment which is used from Edge to Cloud, and throughout your entire IoT project
- Build all kinds of projects from scratch, and easily create attractive user dashboards with widgets based project
- · Easily export your data for BI
- · Be confident that your data is yours

SOFTWARE AND TOOLS

- Octonion software license included
- Six months of Microsoft Azure consumption included to get you started

FLEXIBLE AND SCALABLE

- Built in sensors: 3-axis accelerometer, pressure, temperature, microphone, proximity, light, humidity,
- magnetometer and gyroscope
- Expandable through USB port
- Scale your project from one sensor, to very many sensors

AI STUDIO

- Zero coding approach to train and deploy AI models
- Motion and Vibration Al included
- Edge computing: Al rule and set of data rules at edge level

AI AT THE EDGE

Al is running at the edge, saving energy, bandwidth and time to react



EXAMPLE APPLICATIONS

MARKET	Use case
Utilities, Plant, Machinery	Predictive maintenance of pumps, generators and other remote mechanical systems.
Elevators, Escalators, Travelators	Predictive maintenance, usage patterns and demand planning
Livestock Management	Monitoring of complex motion, as well as temperature, humidity and other parameters can provide livestock wellbeing insights

META SENSING AND PORTAL FEATURES

META SENSING	OCTONION PORTAL
FEATURES	FEATURES
Real time visualisation of Agile	
data:	
Acceleration	
Airhumidity	
Angular velocity	Device management (firmware
Atmospheric pressure	updates) and Device
 Infrared lightness 	provisioning
 Magnetic field 	
Proximity Distance	
Sound Level	
Temperature	
 Visible lightness 	
World acceleration	
Real time visualisation of Agile	
State	
Motion detected (history of	Dashboard with widget display
motion, last detected	of data (adding, removing,
motion, count of detected	resizing, moving of widgets)
motions,)	
Alertsfrom rules	
Battery State	
Data export of recorded data	Smart app: change Portal
session in csv	theme and logo
	API to read data from Portal

End to end IoT solution to deliver AI and security at the edge



SIZE	32mm x17mm x 64mm (w x h l)	
WEIGHT	29q	
OPERATING TEMPERATURE RANGE	-20°C to +60° C	
POWER SUPPLY	Powered by USB connector, or internal rechargeable Li-Poly battery	
BATTERY CAPACITY	260mAh	
ACCELERO/GYRO: Device Magnetic dynamic range Sensitivity	STMicroelectronics LSM6DSLTR ±2/±4/±8/±16 g full scale ±125/±250/±500/±1000/±2000 degree per second (dps) full scale	ľ
MAGNETOMETER Device Magnetic dynamic range Sensitivity	STMicroelectronics LIS2MDLTR ±50 Gauss 1.5 mGauss/LSB ± 7%	15
PRESSURE Device Absolute pressure range Pressure output data rate Pressure accuracy	STMicroelectronics LPS22HBTR 260 to 1260 hPa 75 readings per second ±0.1 hPa after calibration, or ±1 hPa without calibration	/5
TEMPERATURE/HUMIDITY Device Relative humidityrange Relative humidity accuracy Temperature measurement range Temperature accuracy	STMicroelectronics HTS221TR 0 to 100% rH ± 3.5% rH inside 20 to +80% rH range Within Agile operating temperature range ± 0.5 °C,15 to +40 °C	
MEMS MICROPHONE Device Acoustic overload point Signal-to-noise ratio: Sensitivity.	STMicroelectronics MP34DT01TR-M 120 dBSPL 61 dB – 26 dBFS	
AMBIENT LIGHT SENSOR Device Channels Irradiance responsivity (integration time = 400ms, ALS gain = 16x)	ams TSL2540 2 channels; visible and IR light - Visible light (2700K): 363 counts (typ) - IR light (950nm): 352 counts (typ)	
TIME OF FLIGHT SENSOR Device Distance measuring range Maximum measurement rate Typical full field-of-view	STMicroelectronics VL53L1CXV0FY/1 0 to 400 cm Up to 50 measurements/sec 27° field of view	



/SMARTEDGE AGILE HIGHLIGHTS

FEATURES	BENEFITS
Agile meta sensor	Low power meta-sensor is designed to
	be located at the Edge of an IoT
	network. It has 9 built-in sensors types
	(see list below), which are used both to
	learn and build a model, and for
	ongoing monitoring. Default back-end
	connectivity is BLE 5, with other
	connecting options, including
	LoRaWAN and cellular, planned.
Integrated BLE	For flexible, wireless communication via
V5 wireless radio	a gateway to the Cloud.
Internal	For durable, autonomous operation.
rechargeable Li-	
Poly	
battery	
Secure element	Best-in-class security, securing edge to
	cloud, included out-of-the-box



ORDERING INFORMATION

For more product information, please visit : www.element14.com/smartedgeagile

Reach Further

Octonion

CE F©

Avnet part number: AVTSEA01a-M01a-S01a-C00